

Tesla meter

CT-3

- High sensitivity , resolution 0.02 mT (0.2GS)
- Measuring the d.c. flux density and 0~600Hz a.c. flux density
- Measuring ransverse magnetic field (with CT3-1) axial magnetic field (with CT3-2)
- Discriminating N.S polarity of magnetic field
- Power=220V 50Hz or R20(1.5V)x6



 [Operation Manual Download](#)

 [Working Principle Download](#)

CT-5

- Adopted the hall effect principal to measure d.c. flux density
- High precision constant current , Fine stability
- Fast measuring velocity , wide range 0.1m~2.5T
- Measuring transverse magnetic field (with CT5-1) axial magnetic field (with CT3-2)
- Power=220V 50Hz , 5W
- Size Weight=202 x 154 x 80mm , 2Kg



 [Operation Manual Download](#)

 [Working Principle Download](#)

CT-7

- Range : 50mT / 100mT / 250mT / 500mT / 1T
- Accuracy : -2.5%~+2.5% / FS
- Hall probe : may exchange
- Polarity : N.N. may selected



CTS-27

- Range : 0.2T / 1T
- Accuracy : -1.0%~+1.0% Red + 1.0% FS
- Display : 3.5 LED
- Power : 9V (-10%~+10%)
- Size weight : 160 x 88 x 36mm , 325g



 [Operation Manual Download](#)

CST-7

- Ranges : 0.001 / 0.01 / 0.1 / 1Wb(D.C)
- Accuracy : -1%~+1% FS
- Display : 1999LED
- Peak reading hold accuracy : -1%~+1% FS (hold time < 10 Sec)
- Power : 220V 50Hz 8W
- Size Weight : 164 x 214 x 70mm 2Kg









 [Operation Manual Download](#)

CTS-24

- Ranges : 0.1 / 1 / 10 d.c Flux density
- Accuracy : -0.5%~+0.5% Red + 0.5% FS
- Display : 1999 LED
- Power : AC 220V 50Hz 8W
- Size weight : 230 x 291 x 70mm , 2Kg



 [Operation Manual Download](#)

MODEL	NAME	TESTING RANGE	ACCURACY	DISPLAY	SIZE (mm)	WEIGHT (KGS)	OTHER FEATURE	OPERATION MANUAL	WORKING PRINCIPLE
HT200	MINI DIGITAL TESLAMETER	0~1T EXPANDING:100%	+1%-1%	3.5LED	85X160X30				
HT100 HT100-4 HT100-10	DESK DIGITAL TESLAMETE	HT100: 0~0.2T HT100-4: 0~0.4T HT100-10: 0~1T	+1%-1%	3.5LED	210X80X230				
HT500	SIMULATED TESLAMETER	0~2T	+2.5%-2.5%		112X185X70				
CT-7	DC- TESLAMETER	50mT/100mT/250mT /500mT/1T	+2.5%-2.5% FS				POLARITY(N.S.) MAY SELECTED		
CTS-27	DIGITAL TESLAMETER	0.2T/1T	+1.0%-1.0% RED +1.0% FS	3.5LED	160X88X36	0.325	POWER: 9V+10%-10%	 OPERATION MANUAL DOWNLOAD	
CT3-1	AC-DC TESLAMETER	0.1MT~2.5T	0.02MT		265X125X165	3	POWER: 220V 50HZ OR R20(1.5V)X6	 OPERATION MANUALL DOWNLOAD	 WORKING PRINCIPLE DOWNLOAD
		MEASURING TRANSVERSE MAGNETIC FIELD MEASURING D.C. FLUX DENSITY AND 0-600HZ A.C. FLUX DENSITY							
CT3-2	AC-DC TESLAMETER	0.1mT-2.5T	0.02MT		265X125X165	3	DISCLMINATING N.S. POLARITY OF MAGNETIC FIELD	 OPERATION MANUALL DOWNLOAD	
		MEASURING AXIAL MAGNETIC FIELD MEASURING D.C. FLUX DENSITY AND 0-600HZ A.C. FLUX DENSITY							
CT-5	DC- TESLAMETER	0.1mT-2.5T			202X154X80	2	POWER: 220V 50HZ 5W MEASURING TRANSVERSE	 OPERATION MANUALL DOWNLOAD	 WORKING PRINCIPLE DOWNLOAD
		MEASURING TRANSVERSE MAGNETIC FIELD							

TJSH-045	DIGITAL TESLAMETER	0~0.1T/0~1T/0~10T	DC+0.5%-0.5%F.S. AC+1%-1%F.S.	4.5LED	230X290X70	2	AC220" 50HZ 10W		
TJSH-035	DIGITAL TESLAMETER	0~2T/0~2T	DC +1%-1%F.S. AC +2.5%-2.5%F.S.	3.5LED	180X230X100	1.4	AC220" 50HZ 8W		

©Copy Right 2001 YUXIANG All Rights Reserved
Add :Floor 16, Jinyuan plaza, # 57 Hubin nan Road, Xiamen, CHINA 361004
Tel : (86)592 2295387 (86)592 2217138 Fax: (86)592 2207122
Email : yingli@magnets.com.cn or mag@e-magnet.cn